

STK4141 X Series

- ★2ch. /1package, \pm Power Supply
- ★Built-in Muting Circuit
- ★25W/ch. to 70W/ch.
- ★THD = 0.02%

Model	Maximum Ratings 最大定格	Recommended Operating Conditions 推奨動作条件		Operating Characteristics (Recommend Operating Conditions at Test Circuit) 動作特性(Test Circuitにて 推奨動作条件による)			
	Vcc max [V]	Vcc [V]		Po max 1 RL=8Ω f=20 to 20kHz [W]	THD (V _G =40dB) [%]	Po max 2 RL=4Ω f=1kHz [W]	THD (V _G =40dB) [%]
		RL=8Ω	RL=4Ω				
STK4141 X	±41.0	±27.5	±24.5	25 + 25	0.02	25 + 25	0.08
STK4151 X	±42.5	±29.0	±25.5	30 + 30	0.02	35 + 35	0.08
STK4171 X	±49.5	±33.0	±28.5	40 + 40	0.02	45 + 45	0.08
STK4191 X	±53.5	±36.0	±32.5	50 + 50	0.02	55 + 55	0.08
STK4201 X	±57.5	±39.5	-	60 + 60	0.02	-	-
STK4211 X	±62.5	±43.5	-	70 + 70	0.02	-	-

Equivalent Circuit



